
NPD12550 12V55AH




Specifications

No	minal Voltage	12V 55AH		
Rated Ca	pacity (20 hour rate)			
Dimension	Total Height (with terminals)	212mm(8.35inches)		
	Height	208mm(8.19inches)		
	Length	229mm(9.02inches)		
	Width	138mm(5.43inches)		
	Weight	Approx.17.6kg (38.5Ibs)		

Discharge characteristics 77°F (25°C)

•




0

Characteristics

				_			
Сара	ncity	20 hour rate	55AH				
77°F (-	10 hour rate	50AH				
// [(25 ()	5 hour rate	45AH				
Internal F	Resistance	Full charge	8 m Ω				
Canacity	affected	104°F (40°C	102%				
Capacity affected by Temperature (20 hour rate)		77°F (25°C)	100%				
		32°F (0°C)	85%				
		5°F (-15°C)	65%				
Salf Di	charge	Capacity af	91%				
Self-Discharge		Capacity af	82%				
77 F (25 C)	Capacity af	64%				
Standard	Terminal	M6					
Max. Di Current 7		825A (5s)					
		Cranking	Amps				
Cranking	(30-s	ec amps to 7.2V	480A				
Performance (3		Cold Crank	400A				
1	Reserve Capa	city	@ 25Amps	85Min			
(Minute	es to 10.5V at	80°F (27°C)	@ 75Amps	21Min			
Charging (Constant	Cycle	Initial Charging Current 11A Or Small 14.5V~14.9V/77°F (25°C)					
Voltage)	Float	13.6V~13.8V/77°F (25°C)					

Duration of discharge vs. Discharge current



Constant Current Discharge Rating Amperes @ 77 °F (25°C)

Cu	ıt off voltage V/cell	15M	30M	45M	1H	2Н	3Н	5H	8Н	10 H	12H	20H	24H
	1.75V	85	55	41	31.3	16.6	12.5	8.7	6.0	4.95	4.22	2.75	2.30