NPD121050 12V105AH






Specifications


No	minal Voltage	12V		
Rated Ca	pacity (20 hour rate)	105AH		
Dimension	Total Height (with terminals)	215mm(8.46 inches)		
	Height	211mm(8.31 inches)		
	Length	307mm(12.09inches)		
	Width	169mm(6.65inches)		
	Weight	Approx.30.2 kg (66.58Ibs)		

Characteristics


Capacity 77°F(25°C)		20 hour ra	105AH					
		10 hour ra	95AH					
		5 hour ra	86AII					
Internal Resistance			Full charg	4.0m Ω				
Capacity affected by Temperature (20 hour rate)		104°F (40°C	102%					
		77°F (25°C	100%					
		32°F(0°C)	85%					
		5°F (-15°C)	65%					
Self-Discharge 77 F (25°C)		Capacity a	91%					
		Capacity a	82%					
		Capacity a	64%					
Standard Terminal			M6					
Max. Discharge Current 77°F (25°C)		1050A (5s)						
Cranking (Crank 30-sec amps to	660A					
		Cold Cranking Amps (30-sec amps to 7.2V @ 0° F (-18° C)			550A			
Reserve Capacity			ty	@ 25Amps	170Min			
(Minutes to 10.5V at 80°F (27°C)			0°F (27°C)	@ 75Amps	43Min			
Charging (Constant	Су	cle	Initial Cha	mall				
Voltage)	Flo	oat	13.6V∼13.8V/77°F(25°C)					



Discharge characteristics 77°F (25°C)



Duration of discharge vs. Discharge current



Constant Current Discharge Rating Amperes @ 77 °F (25°C)

Cut off voltage V/cell	30M	45M	1H	2Н	3H	5H	8H	10H	12H	20H	24H
1.75V	97.7	72.5	59.6	31.6	23.7	16.7	11.4	9.5	8.1	5.25	4.46