NPD12550 12V55AH






No	minal Voltage	12V		
Rated Ca	pacity (20 hour rate)	55AH		
Dimension	Total Height (with terminals)	212mm(8.35inches)		
	Height	208mm(8.19inches)		
	Length	229mm(9.02inches)		
	Width	138mm(5.43inches)		
	Weight	Approx.17.6kg (38.5Ibs)		


Characteristics

Capacity			20 hour rate	55AH					
77°F (25°C)		10 hour rate	50AH						
		5 hour rate	45AH						
Internal Resistance			Full charge	8m Ω					
Canacity affects			104°F (40°C)	102%					
Capacity affected by Temperature (20 hour rate)		77°F (25°C)	100%						
		32°F (0°C)	85%						
		5°F(-15°C)	65%						
Self-Discharge 77°F (25°C)		Capacity af	91%						
		Capacity af	82%						
		Capacity af	64%						
Standard Terminal			M6						
Max. Discharge			825A (5s)						
Current 77°F(25°C)									
		480A							
Performance				c amps to 7.2V (
			Cold Crank	400A					
			c amps to 7.2V @						
Reserve Capacity			rity	@ 25Amps	85Min				
(Minutes to 10.5V at 80°F (27			80°F (27°C)	@ 75Amps	21Min				
Charging		Cycle	Initial Charging Current 11A Or Small						
(Constant		Cycle	14.5V∼14.9V/77°F (25°C)						
Voltage)		Float	13.6V~13.8V/77°F (25°C)						






Discharge characteristics 77°F (25°C)



Duration of discharge vs. Discharge current



Constant Current Discharge Rating Amperes @ 77 °F (25°C)

Cut off voltage V/cell	15M	30M	45M	1H	2Н	3Н	5H	8Н	10 H	12H	20H	24H
1.75V	85	55	41	31.3	16.6	12.5	8.7	6.0	4.95	4.22	2.75	2.30

Newton Power Deep Cycle Batteries